
MATERIAL SAFETY DATA SHEET

ProX Rocket Motor Reload Kits & Fuel Grains

1.0 PRODUCT / COMPANY IDENTIFICATION

Product Name: Pro29, Pro38, Pro54, Pro75, and Pro98 Rocket Motor Reload Kits

Synonyms: Rocket Motor

Proper Shipping Name: Articles, Explosive, N.O.S. (Ammonium Perchlorate)

Part Numbers: Reload kits: P29R-Y-#G-XX, P38R-Y-#G-XX, P54R-Y-#G-XX,

P29R-Y-#GXL-XX, P38R-Y-#GXL-XX, P54R-Y-#GXL-XX, Propellant grains: P75AC-PG-XX, P98AC-PG-XX, P98AC-MB-PG-XX

Where: V = relead type (A = adjustable delay C = C el

e: Y = reload type (A = adjustable delay, C = C - slot)

= number of grains & XX = propellant type

Product Use: Solid fuel motor for propelling rockets

Manufacturer: Cesaroni Technology Inc.

P.O. Box 246 2561 Stouffville Rd. Gormley, Ont. Canada L0H 1G0

Telephone Numbers:

Product Information: 1-905-887-2370

24 Hour Emergency Telephone Number: 1-613-996-6666 (CANUTEC)

2.0 COMPOSITION / INFORMATION ON INGREDIENTS

Propellant

Ingredient Name	CAS Number	Percentage
Ammonium Perchlorate Metal Powders Synthetic Rubber	7790-98-9	40-85 % 1-45 % 10-30 %

Black Powder Ignition pellet

ingredient Name	CAS Number	Percentage
Potassium Nitrate	7757-79-1	70-76 %
Charcoal	n/a	8-18 %
Sulphur	7704-34-9	9-20 %
Graphite	7782-42-5	trace

3.0 HAZARDS IDENTIFICATION

Emergency Overview:

There articles contain cylinders of ammonium perchlorate composite propellant, encased in inert plastic parts. The forward closure also contains a few grams of black powder. ProX Rocket motor reload kits are classified as explosives, and may cause serious injury, including death if used improperly. All explosives are dangerous and must be handled carefully and used following approved safety procedures under the direction of competent, experienced personnel in accordance with all applicable federal, state and local laws and regulations. Avoid inhaling exhaust products.

General Appearance:

Cardboard tubes contain various plastic parts. Inside the plastic tube are cylinders of composite propellant (rocket fuel). The forward closure also contains a small quantity of black powder. All parts are odourless solids.

Potential Health Effects:

Eye:

Not a likely route of exposure. May cause eye irritation.

Skin:

Not a likely route of exposure. Low hazard for usual industrial/hobby handling.

Ingestion:

Not a likely route of exposure.

Inhalation:

Not a likely route of exposure. May cause respiratory tract irritation. Do not inhale exhaust products.

4.0 FIRST AIR MEAGURES

4.0 FIRST AID MEASURES

Eyes:

Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Skin:

Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid if irritation develops or persists.

Ingestion:

Do NOT induce vomiting. If conscious and alert, rinse mouth and drink 2-4 cupfuls of milk or water.

Inhalation:

Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.

Burns: Burns can be treated as per normal first aid procedures.

5.0 FIRE FIGHTING MEASURES

Extinguishing Media:

In case of fire, use water, dry chemical, chemical foam, or alcohol-resistant foam to contain surrounding fire.

Exposure Hazards During Fire:

Exposure to extreme heat may cause ignition.

Combustion Products from Fire:

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Fire Fighting Procedures:

Keep all persons and hazardous materials away. Allow material to burn itself out. As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.

Special Instructions / Notes:

These articles burn rapidly and generate a significant flame for a short period of time. Black powder is a deflagrating explosive. It is very sensitive to flame and spark and can also be ignited by friction and impact. When ignited unconfined, it burns with explosive violence and will explode if ignited under even slight confinement. Do not inhale exhaust products.

6.0 ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel):

Spills: Clean up spills immediately. Replace articles in packaging and boxes and seal securely. Sweep or scoop up using non-sparking tools.

7.0 HANDLING AND STORAGE

Handling: Keep away from heat, sparks and flame. Avoid contamination. Do not get in eyes, on skin or on clothing. Do not taste or swallow. Avoid prolonged or repeated contact with skin. Follow

manufacturer's instructions for use.

Storage: Store in a cool, dry place away from sources of heat, spark or flame. Keep in shipping packaging

when not in use.

8.0 EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:

Use adequate explosion proof ventilation to keep airborne concentrations low. All equipment and working surfaces must be grounded.

Personal Protective Equipment:

Eyes:

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin:

Clothing should be appropriate for handling pyrotechnic substances.

Clothing:

Clothing should be appropriate for handling pyrotechnic substances.

Respirators:

A respirator is not typically necessary. Follow the OSHA respirator regulations found in

29CFR1910.134 or European Standard EN 149. Always use a NIOSH or European Standard EN 149

approved respirator when necessary.

9.0 PHYSICAL AND CHEMICAL PROPERTIES

Physical State: solid

Appearance: rubber cylinders inside plastic parts

Odour: none
Odour Threshold: Not available.
pH: Not available.
Vapour Pressure: Not available.

Not available. Vapour Density: Not available. Viscosity: Not available. Evaporation Rate: Not available. Boiling Point: Not available. Freezing/Melting Point: Not available. Coefficient of water/oil distribution: Not available. 280°C Autoignition Temperature: Flash Point: Not available.

Explosion Limits, lower (LEL):

Explosion Limits, upper (UEL):

Not available.

Not available.

Not available.

Sensitivity to Mechanical Impact: unprotected black powder can be ignited by impact

Sensitivity to Static Discharge: unprotected black powder can be ignited by static discharge

Decomposition Temperature: > 400°C

Solubility in water: black powder is soluble in water

Specific Gravity/Density: black powder = 1.7-2.1

Propellant = not available

Molecular Formula: Not applicable Molecular Weight: Not applicable.

10.0 STABILITY AND REACTIVITY

Chemical Stability:

Stable under normal temperatures and pressures.

Conditions to Avoid:

Heat, static electricity, friction, impact

Incompatibilities with Other Materials:

Combustible or flammable materials, explosive materials

Hazardous Products Of Decomposition:

Oxides of nitrogen

Hazardous Polymerization:

Will not occur.

11.0 TOXICOLOGICAL INFORMATION

Routes of Entry: Skin contact – not likely

Skin absorption – not likely Eye contact – not likely Inhalation – not likely Ingestion – not likely

Effects of Acute Exposure to Product:

No data available

Effects of Chronic Exposure to Product:

No data available

Exposure Limits:

Black Powder Pellets

Ingredient Name	CAS Number	OSHA PEL	ACGIH TLV
Potassium Nitrate Charcoal Sulphur Graphite	7757-79-1 n/a 7704-34-9 7782-42-5	not established not established not established 2.5 mg/m ³	not established not established not established 15 mmpct (TWA)
Propellant			
Ingredient Name	CAS Number	OSHA PEL	ACGIH TLV
Ammonium Perchlorate metal powder	7790-98-9	not established varies	not established varies

Irritancy of the Product:

No data available

Sensitization to the Product:

No data available

Carcinogenicity:

Synthetic Rubber

Not listed by ACGIH, IARC, NIOSH, NTP, or OSHA

not established

Reproductive Toxicity:

No data available

Teratogenicity:

No data available

Mutagenicity:

No data available Toxically Synergistic Products:

No data available

LD50:

No data available

12.0 ECOLOGICAL INFORMATION

Environmental Data:

Ecotoxicity Data:

Not determined.

EcoFaTE Data:

Not determined.

13.0 DISPOSAL CONSIDERATIONS

Product As Sold: Pack firmly in hole in ground with nozzle pointing up. Ignite motor electrically from a safe

distance and wait 5 minutes before approaching. Dispose of spent components in inert

not established

trash.

Product Packaging: Di

Dispose of used packaging materials in inert trash.

Special Considerations: Consult local regulations about disposal of explosive materials.

14.0 TRANSPORT INFORMATION

Shipping Information - Canada

TDG Classification: Class 1.4 Explosive

Proper Shipping Name: Articles, Explosive, N.O.S. (Model Rocket Motors)

UN Number: 0351
UN Classification Code: 1.4 C
Packing Group: ||
UN Packing Instruction: 101

Shipping Information - USA / IMO

Proper Shipping Name: Articles, Explosive, N.O.S. (Model Rocket Motors)

UN Number: 0351 UN Classification Code: 1.4 C

DOT / IMO Label: Class 1 – Explosive – Division 1.4C

Shipping Information - IATA

Proper Shipping Name: Articles, Explosive, N.O.S. (Model Rocket Motors)

UN Number: 0351 UN Classification Code: 1.4 C

IATA Labels: Class 1 – Explosive – Division 1.4C

Cargo Aircraft Only

15.0 REGULATORY INFORMATION

Canada

This product has been classified according to the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

WHMIS Classification: Not Controlled (explosive)

Domestic Substance List (DSL) Status:

All ingredients are listed on Canada's DSL List.

Canadian Explosives Classification: Class 7.2.5

This product is an authorized explosive in Canada.

These products are not considered "Controlled Good" in Canada under the Controlled Goods Regulations.

United States of America

TSCA Inventory Status:

All ingredients are listed on the TSCA inventory.

Hazardous Chemical Lists

CERCLA Hazardous Substance (40 CFR 302.4)

SARA Extremely Hazardous Substance (40 CFR 355)

No SARA Toxic Chemical (40 CFR 372.65)

No

European/International Regulations

The product on this MSDS, or all its components, is included on the following countries' chemical inventories: EINECS – European Inventory of Existing Commercial Chemical Substances

European Labelling in Accordance with EC Directives

Hazard Symbols: Explosive.

Risk Phrases:

R 2 Risk of explosion by shock, friction, fire or other sources of ignition.

R 11 Highly flammable

R 44 Risk of explosion if heated under confinement.

Safety Phrases:

\$ 1/2 Keep locked up and out of the reach of children.

\$ 8\$ 15Keep container dry.Keep away from heat.

\$ 16 Keep away from sources of ignition -- No smoking.

Version 2.02 Revision Date. 8 Feb 2010

S 17 Keep away from combustible material.
S 18 Handle and open container with care.
S 33 Take precautionary measures against static discharges.
S 41 In case of fire and/or explosion do not breathe fumes.

16.0 OTHER INFORMATION

MSDS Prepared by: Regulatory Affairs Department

Cesaroni Technology Inc. P.O. Box 246 2561 Stouffville Rd. Gormley, ON

Canada L0H 1G0

Telephone: 905-887-2370 x239 Fax: 905-887-2375

Web Sites: <u>www.cesaronitech.com</u>

www.Pro38.com

The data in this Material Safety Data Sheet relates only to the specific material or product designated herein and does not relate to use in combination with any other material or in any process.

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if the company has been advised of the possibility of such damages.